

Ambu[®] BlueSensor P

ECG Electrode - Single-use



Key Benefits

- Highly conductive wet gel
- Superior adhesion
- Comfortable foam backing
- Unique offset connector
- High-quality Ag/AgCl sensor

Ambu[®] BlueSensor P

The small Ambu BlueSensor P features highly conductive wet gel, offset connector and superior adhesion to ensure optimal signal quality during short- to medium-term applications. It can be used on adults and children. Thanks to the comfortable foam backing material, the electrode is easy to use and gentle to the skin.



Wet gel



Foam backing

BlueSensor

Ambu^{*}
Ideas that work for life

Specifications

Dimensions	
Electrode size (max. L x W or diameter in mm)	40.8 x 34
Skin contact size (max. L x W or diameter in mm)	34
Adhesive area (in mm ²)	754
Height excluding connector/wire (in mm)	1.6
Sensor	
Sensor material	Silver/silver chloride
Gel system	Wet gel
Sensor area (in mm ²)	10
Gel area (in mm ²)	154
Electrical data (ANSI/AAMI)	
AC impedance - typical	700 Ω
DC offset voltage - typical	0.4 mV
Defibrillation overload recovery - typical	11.1 mV
Rate of change of polarization potential - typical	0.2 mV/s
Combined offset instability and internal noise	<15μV
Bias current tolerance (over 8 hours)	<5 mV

Materials

Electrode	
Bio-compatible	Yes
Sensor	Silver/silver chloride (Ag/AgCl)
Sponge	Polyurethane foam (PUR)
Outer carrier	Polyvinyl chloride foam (PVC)
Outer adhesive	Acrylate
Inner carrier (if any)	-
Inner adhesive (if any)	-
Upper part	Polyvinyl chloride film (PVC)
Fitting	Polypropylene (PP)
Connector (stud)	Stainless steel
Eyelet	Silver coated plastic
Lead wire core	-
Lead wire insulation	-
Lead wire connector	-
Liner	Polyester/polyethylene film (PET/PE)

Available configurations*

Product	Pack
P-00-S/10	10
P-00-S/50	50

Ambu USA
 6230 Old Dobbin Lane
 Columbia, MD 21045
 Tel. 800 262 8462
 Fax 800 262 8673
 www.ambuUSA.com

Environment	
PVC-free electrode	No
PVC-free lead wire	-
Wire not made with natural rubber latex	
PVC-free packaging	Yes
X-Ray & MRI	
Radiolucent	No
MR Conditional	No
Shelf life	
Opened pouches	1 month
Unopened pouches*	15 months

*from date of production

Connectors



S = Stud

Packaging	
Pouches, inner layer	Polyethylene (PE)
Pouches, center layer	Aluminium (Al)
Pouches, outer layer	Polyester (PET)
Boxes	Cardboard
Standard Packaging	
Quantity/liner	1
Quantity/pouch	10, 50
Quantity/box	960/1920, 1000/2000

Options	
Connectors	S
Precaution	
Single-use only	

CE US: Rx only