

Ambu® BlueSensor BRS

ECG Electrode - Single use



Key Benefits

- Skin-friendly solid gel
- Soft cloth backing material
- Small size ideal for neonatal patients
- Radiolucent
- Special shape for improved adhesion


Ambu® BlueSensor BRS

The tiny radiolucent Ambu BlueSensor BRS has been specially developed for babies and newborns. The electrode features a skin-friendly solid gel that ensures optimal signal quality monitoring, and also allows the electrode to be repositioned if necessary.

Thanks to the soft material the electrode remains comfortable to wear over long periods. The BRS is only available with preattached lead wires (color-coding optional).



Solid gel



Cloth backing



Radiolucent

BlueSensor

Ambu
Ideas that work for life

Specifications

Dimensions	
Electrode size (L x W in mm)	16 x 19
Skin contact size (L x W in mm)	16 x 19
Adhesive area (in mm ²)	269
Height excluding connector/wire (in mm)	1
Sensor	
Sensor material	Silver/silver chloride
Gel system	Solid gel
Sensor area (in mm ²)	269
Gel area/measuring area (in mm ²)	269
Electrical data (ANSI/AAMI)	
AC impedance - typical	600 Ω
DC offset voltage - typical	0.6 mV
Defibrillation overload recovery - typical	14.3 mV
Rate of change of polarization potential	0.5 mV/s
Combined offset instability and internal noise	<90 μV
Bias current tolerance (over 8 hours)	<30 mV

Materials

Electrode	
Bio-compatible	Yes
Sensor	Silver/silver chloride (Ag/AgCl)
Sponge	-
Outer carrier	Carbon-filled polyvinyl chloride
Outer adhesive	Solid gel
Inner carrier (if any)	-
Inner adhesive (if any)	-
Upper part	Non-woven polyester cloth
Fitting	-
Connector (stud)	-
Lead wire core	Carbon
Lead wire insulation	Polyvinyl chloride (PVC)
Lead wire connector	Brass/polypropylene (PP)
Liner	Siliconized polyester film

Environment	
PVC-free electrode	No
Electrode not made with natural rubber latex	
PVC-free lead wire	No
Wire not made with natural rubber latex	
PVC-free packaging	Yes
X-Ray & MRI	
Radiolucent	Yes
MR Conditional	No
Shelf life	
Opened pouches	1 month
Unopened pouches*	18 months

*from date of production

Connectors



K = 1.5 mm connector

Packaging	
Pouches, inner layer	Polyethylene (PE)
Pouches, center layer	Aluminium (Al)
Pouches, outer layer	Polyester (PET)
Boxes	Cardboard
Standard Packaging	
Quantity/liner	3
Quantity/pouch	3, 12
Quantity/box	600/1200
Minimum sales	3, 12
Options	
Connectors	-
Pre-wired	Yes
Pre-wired connectors	K
Precaution	
Single use only	

Available configurations*

Product	Pack	Box	Case
BR-50-A/12	12	600	1200
BR-50-K/3	3	600	1200
BR-50-K/US/3*	3	600	1200
BR-80-K/12	12	600	1200
BR-80-A/12	12	600	1200
BRS-50-K/12	12	600	1200
BRS-50-K/US/3*	3	600	1200

Ambu USA
 6230 Old Dobbin Lane
 Columbia, MD 21045
 Tel. 800 262 8462
 Fax 800 262 8673
 www.ambuUSA.com

CE US: Rx only