

Ambu® aScope™ 5 Broncho 4.2/2.2

DATASHEET

aScope 5 Broncho combines the high level of maneuverability and imaging needed in the bronchoscopy intensive care unit and operating room suite with the sterility and efficiency of the single-use concept. The result? Consistently high performance, sterility, and the flexibility required for a complex and demanding workflow.

Single-use like you've never seen it before

With the launch of the 5th generation of aScope Broncho, Ambu takes single-use bronchoscopy to even greater heights.

Building on over a decade of single-use bronchoscopy know-how, aScope 5 Broncho combines the familiar benefits of reusable scopes with the advantages of the single-use solution. It is compatible with the Ambu® aBox™ 2 and Ambu® aView™ 2 Advance displaying and processing units and can easily be connected to external monitors.

aScope 5 Broncho delivers consistently high performance with excellent maneuverability, next-level imaging and a smart, functional design. This level of performance is complemented by the sterility and efficiency of the Ambu single-use solution to give you the quality and flexibility you need for a complex and demanding workflow in the bronchoscopy suite.



KEY BENEFITS

Eliminate the need for endoscope reprocessing and repairs

Start or expand bronchoscopy services with minimal capital investment

Easily navigate bronchial segments with bending angles of 210°/210° (up/down)

Designed for smooth insertion and positioning of endotherapy instruments

Choose the right endotherapy instrument without fear of damaging an expensive scope

Visualize the bronchial tree clearly with the system delivering high image quality

Seamlessly integrate Ambu displaying and processing units to your documentation systems

Offer your patient a sterile scope and eliminate the risk of cross-contamination

*aScope 5 Broncho and display devices may not be available in all countries, please contact your local Ambu representative.

Ambu

SPECIFICATIONS

Optical system

Field of view	120°
Direction of view	0° (forward viewing)
Depth of field	3 - 100 mm
Illumination method	LED
Camera sensor module	CMOS

Insertion portion

Bending section	210° up, 210° down
Insertion cord diameter	4.2 mm (0.17")
Distal tip diameter	4.4 mm (0.17")
Maximum diameter of insertion portion	Max. Ø 4.8 mm (0.19")
Minimum endotracheal tube size (inner diameter)	5.0 mm/15 Fr
Working length	600 mm (23.6")
Rotary function	120° left/right
Depth marks	Every 5 cm

Working channel

Instrument channel width	2.2 mm (0.09")
Minimum instrument channel width*	Min. Ø 2.15 mm (0.08")

Suction connector

Connecting tube inner diameter	Ø 5.5 - 9.0 mm
--------------------------------	----------------

Operating environment, storage, and transportation

Temperature - transportation	-10 - 55 °C (14 to 131 °F)
Temperature - operating environment	10 - 40 °C (50 to 104 °F)
Temperature - storage	10 - 25 °C (50 to 77 °F)
Relative humidity - storage	10 - 85 %
Atmospheric pressure - storage	50 - 106 kPa

Sterilization

Method of sterilization	ETO
-------------------------	-----

Other

Compatibility	Cryobiopsy probes
Latex, phthalate and PVC free	Yes

ORDERING SPECIFICATIONS

Item no.	Quantity (Ambu® aScope™ 5 Broncho 4.2/2.2)
620001000US	5/box

* There is no guarantee that accessories selected solely using this minimum instrument channel width will be compatible in combination.



aScope 5 Broncho 4.2/2.2 is compatible with endotherapy instruments designed to fit a working channel diameter of up to 2.2 mm.

Questions? Contact your Ambu representative at 800-262-8462 or visit www.ambuUSA.com

Ambu FOREVER FORWARD

Ambu, Inc.
6721 Columbia Gateway Drive, Suite 200
Columbia, Maryland 21046
Tel. 800 262 8462
Fax 800 262 8673
ambuUSA.com

CE₂₇₉₇ US: Rx only