


Ambu® Neuroline Monopolar Needles



Key Benefits

- Tip superior in its sharpness for low penetration resistance
- Extra-smooth coating for low friction and improved patient comfort
- Ergonomic hub design for easy and secure grip
- Wide range of color-coded sizes to meet your needs
- Available with or without pre-attached lead wire

Recommended applications

- Electromyography (EMG)

Ambu® Neuroline Monopolar Needles

Ambu Neuroline Monopolar needles provide low penetration resistance thanks to the sharp design. Moreover, the needles have a smooth surface coating which reduces friction when inserting and working in the target area. This significantly improves patient comfort.

The needles feature a color-coded ergonomic hub, which is both ribbed and concave to provide better control and tactile feedback. The needles are made of stainless steel and feature an optimal combination of strength and flexibility.

Strength ensures that you quickly and efficiently penetrate the skin; flexibility facilitates fine adjustments within the target area. Our needles are available both with and without a pre-attached lead wire.

Ambu also offers an Ambu Neuroline Monopolar cable with a 76 cm (30") lead wire.

Specifications

Environment	
PVC-free electrode	No
Latex-free electrode	Yes
PVC-free lead wire	No
Latex-free lead wire	Yes
PVC-free packaging	Yes

Materials

Description	Electrode without lead wire	Electrode with lead wire
Needle	Stainless steel	Stainless steel
Coating	Low friction polymer	Low friction polymer
Hub	Copolymer of Acrylonitrile, Butadiene, and Styrene (ABS)	Copolymer of Acrylonitrile, Butadiene, and Styrene (ABS)
Lead wire		Flexible Copper wire with PVC insulation
Connector	Stainless steel	Brass
Plastic protector	Polyethylene (PE)	Polyethylene (PE)
Connection type	1.0 Pin - connector	1.5 mm touch-proof (DIN 42 802)
Sterilization method	EO-sterilized	EO-sterilized

Packaging	
Pouches, transparent layer	Polyester (PET)
Pouches, centre layer	Polypropylene (PP)
Pouches, paper layer	Paper
Boxes	Cardboard

Available configurations

Item No.	Length		Caliber		Shelf life in months (unopened pouches)	Packaging		
	mm	inch	mm	n° calibre		pouch	box	carton
■ 742 25-36/40	25	1"	0.36	28G	36	1	40	320
■ 742 38-36/40	38	1.5"	0.36	28G	36	1	40	320
■ 742 38-45/40	38	1.5"	0.45	26G	36	1	40	320
■ 742 50-45/40	50	2"	0.45	26G	36	1	40	320
■ 742 75-50/40	75	3"	0.50	25G	36	1	40	320
■ 743 25-36/40	25	1"	0.36	28G	36	1	40	320
■ 743 38-36/40	38	1.5"	0.36	28G	36	1	40	320
■ 743 38-45/40	38	1.5"	0.45	26G	36	1	40	320
■ 743 50-45/40	50	2"	0.45	26G	36	1	40	320
■ 743 75-50/40	75	3"	0.50	25G	36	1	40	320

Pre-attached lead wire: 76 cm (30")

Available cables

Item No.	Lead wire length		Shelf life in months unopened pouches	Needle socket mm	Connector mm	Packaging pouch
□ 1744	76	30"	-	1.0	1.5 (DIN 42 802)	1

The reusable Ambu Neuroline Monopolar cable has an orientation-free connection to the needle, strong flexible wire and fits most EMG equipment.

Directions



1. Peel the sterile pouch open and remove the single patient needle electrode.
2. Connect the single patient needle electrode to the equipment.
3. Remove the protective tube.
4. After use, dispose of the needle electrode in a designated container. The needle electrodes are for single patient use only. However, the electrodes may be used more than once on the patient during the examination.

Ambu USA
6230 Old Dobbin Lane
Columbia, MD 21045
Tel. 800 262 8462
Fax 800 262 8673
ambuUSA.com

Connectors



K = 1.5 mm connector



Storage temperature

Precautions

Single Patient EMG needle electrodes are for single patient use only. Do not re-use or re-sterilize.